



Service Performance Indicator Definitions (PID)

14-State 271 PID Version 7.18.0

QWEST'S SERVICE PERFORMANCE INDICATOR DEFINITIONS (PID)

14-State 271 PID Version ~~7.18.0~~

Introduction

Qwest will report performance results for the service performance indicators defined herein. Qwest will report separate performance results associated with the services it provides to Competitive Local Exchange Carriers (CLECs) in aggregate (except as noted herein), to CLECs individually and, as applicable, to Qwest's retail customers in aggregate. Within these categories, performance results related to service provisioning and repair will be reported for the products listed in each definition. Reports for CLECs individually will be subject to agreements of confidentiality and/or nondisclosure.

The definitions in this version of the PID apply in the 14 states of Qwest's local service region: Arizona, Colorado, Idaho, Iowa, Minnesota, Montana, Nebraska, New Mexico, North Dakota, Oregon, South Dakota, Utah, Washington and Wyoming. Individual state Performance Assurance Plans may specify and apply state specific variations from the Performance Measure definitions and/or standards contained herein.

Qwest's Service Performance Indicator Definitions

Table of Contents

ELECTRONIC GATEWAY AVAILABILITY	1
GA-1 – Gateway Availability – IMA-GUI.....	1
GA-2 – Gateway Availability – IMA-EDI.....	<u>212</u>
GA-3 – Gateway Availability – EB-TA.....	<u>313</u>
GA-4 – System Availability – EXACT.....	<u>414</u>
GA-6 – Gateway Availability – GUI – Repair.....	<u>515</u>
GA-7 – Timely Outage Resolution following Software Releases.....	<u>616</u>
PRE-ORDER/ORDER	<u>717</u>
PO-1 – Pre-Order/Order Response Times.....	<u>717</u>
PO-2 – Electronic Flow-through.....	<u>10110</u>
PO-3 – LSR Rejection Notice Interval.....	<u>12112</u>
PO-4 – LSRs Rejected.....	<u>13113</u>
PO-5 – Firm Order Confirmations (FOCs) On Time.....	<u>14114</u>
PO-6 – Work Completion Notification Timeliness.....	<u>17117</u>
PO-7 – Billing Completion Notification Timeliness.....	<u>18118</u>
PO-8 – Jeopardy Notice Interval.....	<u>20120</u>
PO-9 – Timely Jeopardy Notices.....	<u>21121</u>
PO-15 – Number of Due Date Changes per Order.....	<u>22122</u>
PO-16 – Timely Release Notifications.....	<u>23123</u>
PO-19 – Stand-Alone Test Environment (SATE) Accuracy.....	<u>25125</u>
PO-20 (Expanded) – Manual Service Order Accuracy.....	<u>28128</u>
ORDERING AND PROVISIONING	<u>35135</u>
OP-2 – Calls Answered within Twenty Seconds – Interconnect Provisioning Center.....	<u>35135</u>
OP-3 – Installation Commitments Met.....	<u>36136</u>
OP-4 – Installation Interval.....	<u>39139</u>
OP-5 – New Service Quality.....	<u>42142</u>
OP-6 – Delayed Days.....	<u>47147</u>
OP-7 – Coordinated “Hot Cut” Interval – Unbundled Loop.....	<u>50150</u>
OP-8 – Number Portability Timeliness.....	<u>51151</u>
OP-13 – Coordinated Cuts On Time – Unbundled Loop.....	<u>52152</u>
OP-15 – Interval for Pending Orders Delayed Past Due Date.....	<u>54154</u>
OP-17 – Timeliness of Disconnects associated with LNP Orders.....	<u>57157</u>
MAINTENANCE AND REPAIR	<u>59159</u>
MR-2 – Calls Answered within 20 Seconds – Interconnect Repair Center.....	<u>59159</u>
MR-3 – Out of Service Cleared within 24 Hours.....	<u>60160</u>
MR-4 – All Troubles Cleared within 48 hours.....	<u>62162</u>
MR-5 – All Troubles Cleared within 4 hours.....	<u>64164</u>
MR-6 – Mean Time to Restore.....	<u>66166</u>
MR-7 – Repair Repeat Report Rate.....	<u>69169</u>
MR-8 – Trouble Rate.....	<u>72172</u>
MR-9 – Repair Appointments Met.....	<u>7517574</u>
MR-10 – Customer and Non-Qwest Related Trouble Reports.....	<u>7617675</u>
MR-11 – LNP Trouble Reports Cleared within 24 Hours.....	<u>7817877</u>
BILLING	<u>8018079</u>
BI-1 – Time to Provide Recorded Usage Records.....	<u>8018079</u>

Table of Contents (continued)

BI-2 – Invoices Delivered within 10 Days.....	<u>8118180</u>
BI-3 – Billing Accuracy – Adjustments for Errors	<u>8218281</u>
BI-4 – Billing Completeness.....	<u>8318382</u>
DATABASE UPDATES.....	<u>8418483</u>
DB-1 – Time to Update Databases	<u>8418483</u>
DB-2 – Accurate Database Updates.....	<u>8618685</u>
DIRECTORY ASSISTANCE.....	<u>8718786</u>
DA-1 – Speed of Answer – Directory Assistance.....	<u>8718786</u>
OPERATOR SERVICES	<u>8818887</u>
OS-1 – Speed of Answer – Operator Services	<u>8818887</u>
NETWORK PERFORMANCE	<u>8918988</u>
NI-1 – Trunk Blocking	<u>8918988</u>
NP-1 – NXX Code Activation	<u>9119190</u>
COLLOCATION	<u>9319392</u>
CP-1 – Collocation Completion Interval	<u>9319392</u>
CP-2 – Collocations Completed within Scheduled Intervals	<u>9619695</u>
CP-3 – Collocation Feasibility Study Interval	<u>99199</u>
CP-4 – Collocation Feasibility Study Commitments Met.....	<u>1001100</u>
DEFINITION OF TERMS	<u>1011101</u>
GLOSSARY OF ACRONYMS.....	<u>1051105</u>
APPENDIX A.....	<u>1071107</u>

Electronic Gateway Availability

GA-1 – Gateway Availability – IMA-GUI

<p>Purpose: Evaluates the quality of CLEC access to the IMA-GUI electronic gateway and one associated system, focusing on the extent they are actually available to CLECs.</p>	
<p>Description: GA-1A: Measures the availability of the IMA-GUI (Interconnect Mediated Access- Graphical User Interface), and reports the percentage of Scheduled Availability Time the IMA-GUI interface is available for view and/or input.</p> <ul style="list-style-type: none"> • Scheduled Up Time hours for preorder, order, and provisioning transactions are based on the currently published hours of availability found on the following website: http://www.qwest.com/wholesale/cmp/ossHours.html. <p>GA-1D: Measures the availability of the SIA system, which facilitates access for the IMA-GUI interface and the IMA-EDI interface (see GA-2), and reports the percentage of scheduled time the SIA system is available. Scheduled availability times will be no less than the same hours as listed for IMA-GUI and IMA-EDI.</p> <ul style="list-style-type: none"> • Time Gateway is Available to CLECs is equal to Scheduled Availability Time minus Outage Time. • Scheduled Availability Time is equal to Scheduled Up Time minus Scheduled Down Time. • Scheduled Down Time is time identified and communicated that the interface is not available due to maintenance and/or upgrade work. Notification of Scheduled Down Time for routine maintenance and/or upgrade work will be provided no less than 48 hours in advance. • An outage is a critical or serious loss of functionality, attributable to the specified gateway or component (i.e., IMA-GUI, SIA), affecting Qwest's ability to serve its customers. An outage is determined by Qwest technicians through the use of verifiable data, collected from the affected customer(s) and/or from mechanized event management systems. 	
<p>Reporting Period: One month</p>	<p>Unit of Measure: Percent</p>
<p>Reporting Comparisons: CLEC aggregate results</p>	<p>Disaggregation Reporting: Region-wide level. Results will be reported as follows: GA-1A IMA Graphical User Interface Gateway GA-1D SIA system</p>
<p>Formula: $\left(\frac{\text{[Number of Hours and Minutes Gateway is Available to CLECs During Reporting Period]}}{\text{[Number of Hours and Minutes of Scheduled Availability Time During Reporting Period]}} \right) \times 100$ </p>	
<p>Exclusions: None</p>	
<p>Product Reporting: None</p>	<p>Standard: 99.25 percent</p>
<p>Availability: Available</p>	<p>Notes:</p>

GA-2 – Gateway Availability – IMA-EDI

Purpose: Evaluates the quality of CLEC access to the IMA-EDI electronic gateway, focusing on the extent the gateway is actually available to CLECs.	
Description: Measures the availability of IMA-EDI (Interconnect Mediated Access - Electronic Data Interchange) interface and reports the percentage of scheduled availability time the IMA-EDI Interface is available for view and/or input. All times during which the interface is scheduled to be operating during the reporting period are measured. <ul style="list-style-type: none"> • Scheduled Up Time hours for IMA-EDI based on the currently published hours of availability found on the following website: http://www.qwest.com/wholesale/cmp/ossHours.html. Time Gateway is Available to CLECs is equal to Scheduled Availability Time minus Outage Time. • Scheduled Availability Time is equal to Scheduled Up Time minus Scheduled Down Time. • Scheduled Down Time is time identified and communicated that the interface is not available due to maintenance and/or upgrade work. Notification of Scheduled Down Time for routine maintenance and/or upgrade work will be provided no less than 48 hours in advance. • An outage is a critical or serious loss of functionality, attributable to the specified gateway or component (i.e., IMA-EDI), affecting Qwest's ability to serve its customers. An outage is determined by Qwest technicians through the use of verifiable data, collected from the affected customer(s) and/or from mechanized event management systems. 	
Reporting Period: One month	Unit of Measure: Percent
Reporting Comparisons: CLEC aggregate results	Disaggregation Reporting: Region-wide level. (See GA-1D for reporting of SIA system availability.)
Formula: ([Number of Hours and Minutes Gateway is Available to CLECs During Reporting Period] ÷ [Number of Hours and Minutes of Scheduled Availability Time During Reporting Period]) x 100	
Exclusions: None	
Product Reporting: None	Standard: 99.25 percent
Availability: Available	Notes:

GA-3 – Gateway Availability – EB-TA

Purpose: Evaluates the quality of CLEC access to the EB-TA interface, focusing on the extent the gateway is actually available to CLECs.	
Description: Measures the availability of EB-TA (Electronic Bonding – Trouble Administration) interface and reports the percentage of scheduled availability time the EB-TA Interface is available. <ul style="list-style-type: none"> • Scheduled Up Time hours are based on the currently published hours of availability found on the following website: http://www.qwest.com/wholesale/cmp/ossHours.html. • Time Gateway is Available to CLECs is equal to Scheduled Availability Time minus Outage Time. • Scheduled Availability Time is equal to Scheduled Up Time minus Scheduled Down Time. • Scheduled Down Time is time identified and communicated that the interface is not available due to maintenance and/or upgrade work. Notification of Scheduled Down Time for routine maintenance and/or upgrade work will be provided no less than 48 hours in advance. • An outage is a critical or serious loss of functionality, attributable to the specified gateway or component (i.e., EB-TA), affecting Qwest's ability to serve its customers. An outage is determined by Qwest technicians through the use of verifiable data, collected from the affected customer(s) and/or from mechanized event management systems. 	
Reporting Period: One month	Unit of Measure: Percent
Reporting Comparisons: CLEC aggregate results	Disaggregation Reporting: Region-wide level.
Formula: $([\text{Number of Hours and Minutes Gateway is Available to CLECs During Reporting Period}] \div [\text{Number of Hours and Minutes of Scheduled Availability During Reporting Period}]) \times 100$	
Exclusions: None	
Product Reporting: None	Standard: 99.25 percent
Availability: Available	Notes:

GA-4 – System Availability – EXACT

Purpose: Evaluates the quality of CLEC batch access to the EXACT electronic access service request system, focusing on the extent the system is actually available to CLECs.	
Description: Measures the availability of EXACT system and reports the percentage of scheduled availability time the EXACT system is available. <ul style="list-style-type: none"> Scheduled Up Time hours are based on the currently published hours of availability found on the following website: http://www.qwest.com/wholesale/cmp/ossHours.html. Time System is Available to CLECs is equal to Scheduled Availability Time minus Outage Time. Scheduled Availability Time is equal to Scheduled Up Time minus Scheduled Down Time. Scheduled Down Time is time identified and communicated that the system is not available due to maintenance and/or upgrade work. Notification of Scheduled Down Time for routine maintenance and/or upgrade work will be provided no less than 48 hours in advance. An outage is a critical or serious loss of functionality, attributable to the specified gateway or component (i.e., EXACT), affecting Qwest's ability to serve its customers. An outage is determined by Qwest technicians through the use of verifiable data, collected from the affected customer(s) and/or from mechanized event management systems. 	
Reporting Period: One month	Unit of Measure: Percent
Reporting Comparisons: CLEC aggregate results	Disaggregation Reporting: Region-wide level.
Formula: $([\text{Number of Hours and Minutes EXACT is Available to CLECs During Reporting Period}] \div [\text{Number of Hours and Minutes of Scheduled Availability During Reporting Period}]) \times 100$	
Exclusions: None	
Product Reporting: None	Standard: 99.25 percent
Availability: Available	Notes:

GA-6 – Gateway Availability – GUI -- Repair

Purpose: Evaluates the quality of CLEC access to the GUI Repair electronic gateway, focusing on the extent the gateway is actually available to CLECs.	
Description: Measures the availability of the GUI (Graphical User Interface) repair electronic interface and reports the percentage of scheduled availability time the interface is available for view and/or input. All times during which the interface is scheduled to be operating during the reporting period are measured. <ul style="list-style-type: none"> • Scheduled Up Time” hours are based on the currently published hours of availability found on the following website: http://www.qwest.com/wholesale/cmp/ossHours.html. • Time Gateway is Available to CLECs is equal to Scheduled Availability Time minus Outage Time. • Scheduled Availability Time is equal to Scheduled Up Time minus Scheduled Down Time. • Scheduled Down Time is time identified and communicated that the interface is not available due to maintenance and/or upgrade work. Notification of Scheduled Down Time for routine maintenance and/or upgrade work will be provided no less than 48 hours in advance. • An outage is a critical or serious loss of functionality, attributable to the specified gateway or component (i.e., GUI-Repair), affecting Qwest’s ability to serve its customers. An outage is determined by Qwest technicians through the use of verifiable data, collected from the affected customer(s) and/or from mechanized event management systems. 	
Reporting Period: One month	Unit of Measure: Percent
Reporting Comparisons: CLEC aggregate results	Disaggregation Reporting: Region-wide level.
Formula: [Number of Hours and Minutes Gateway is Available to CLECs During Reporting Period ÷ Number of Hours and Minutes of Scheduled Availability Time During Reporting Period] x 100	
Exclusions: None	
Product Reporting: None	Standard: 99.25 percent
Availability: Available	Notes:

GA-7 – Timely Outage Resolution following Software Releases

Purpose: Measures the timeliness of resolution of gateway or system outages attributable to software releases for specified OSS interfaces, focusing on CLEC-affecting software releases involving the specified gateways or systems.	
Description: <ul style="list-style-type: none"> Measures the percentage of gateway or system outages, which are attributable to OSS system software releases and which occur within two weeks after the implementation of the OSS system software releases, that are resolved ^{NOTE 1} within 48 hours of detection by the Qwest monitoring group or reporting by a CLEC/co-provider. Includes software releases associated with the following OSS interfaces in Qwest: IMA-GUI, IMA-EDI, and CEMR, Exchange Access, Control, & Tracking (EXACT) ^{NOTE 2}, Electronic Bonding– Trouble Administration (EB -TA) ^{NOTE 3} An outage for this measurement is a critical or serious loss of functionality, attributable to the specified gateway or component, affecting Qwest’s ability to serve its customers or data loss ^{NOTE 4} on the Qwest side of the interface. An outage is determined by Qwest technicians through the use of verifiable data, collected from the affected customer(s) and/or from mechanized event management systems. The outage resolution time interval considered in this measurement starts at the time Qwest’s monitoring group detects a failure, or at the date/time of the first transaction sent to Qwest that cannot be processed (i.e. lost data), and ends with the time functionality is restored or the lost data is recovered. 	
Reporting Period: Monthly	Unit of Measure: Percent
Reporting Comparisons: CLEC Aggregate	Disaggregation Reporting: Region-wide level.
Formula: $\left[\frac{\text{Total outages detected within two weeks of a Software Release that are resolved within 48 hours of the time Qwest detects the outage}}{\text{Total number of outages detected within two weeks of Software Releases resolved in the Reporting Period}} \right] \times 100$	
Exclusions: <ul style="list-style-type: none"> Outages in releases prior to any CLEC migrating to the release. Duplicate reports attributable to the same software defect. 	
Product Reporting: None	Standards: Volume = 1-20: 1 miss Volume > 20: 95%
Availability: Available	Notes: <ol style="list-style-type: none"> “Resolved” means that service is restored to the reporting CLEC, as experienced by the CLEC. EXACT is a Telecordia system. Only releases for changes initiated by Qwest for hardware or connectivity will be included in this measurement. Outages reported under EB-TA are the same as outages in MEDIACC. For data loss to be considered for GA-7, a functional acknowledgement must have been provided for the data in question (e.g., EDI 997, LSR ID or trouble ticket number).

Pre-Order/Order

PO-1 – Pre-Order/Order Response Times

Purpose:

Evaluates the timeliness of responses to specific preordering/ordering queries for CLECs through the use of Qwest's Operational Support Systems (OSS). Qwest's OSS are accessed through the specified gateway interface.

Description:**PO-1A & PO-1B:**

Measures the time interval between query and response for specified pre-order/order transactions through the electronic interface.

- Measurements are made using a system that simulates the transactions of requesting pre-ordering/ordering information from the underlying existing OSS. These simulated transactions are made through the operational production interfaces and existing systems in a manner that reflects, in a statistically-valid manner, the transaction response times experienced by CLEC service representatives in the reporting period.
- The time interval between query and response consists of the period from the time the transaction request was "sent" to the time it is "received" via the gateway interface.
- A query is an individual request for the specified type of information.

PO-1C:

- Measures the percentage of all IRTM Queries measured by PO-1A & 1B transmitted in the reporting period that timeout before receiving a response.

PO-1D:

- Measures the average response time for a sampling of rejected queries across preorder transaction types. The response time measured is the time between the issuance of a pre-ordering transaction and the receipt of an error message associated with a "rejected query." A rejected query is a transaction that cannot be successfully processed due to the provision of incomplete or invalid information by the sender, which results in an error message back to the sender. ^{NOTE 1}

Reporting Period: One month**Unit of Measure:**

PO-1A, PO-1B, & PO-1D: Seconds
PO-1C: Percent

PO-1 – Pre-Order/Order Response Times (continued)

<p>Reporting Comparisons: CLEC aggregate.</p>	<p>Disaggregation Reporting: Region-wide level. Results are reported as follows: PO-1A Pre-Order/Order Response Time for IMA-GUI PO-1B Pre-Order/Order Response Time for IMA-EDI Results are reported separately for each of the following transaction types: ^{NOTE 2}</p> <ol style="list-style-type: none"> 1. Appointment Scheduling (Due Date Reservation, where appointment is required) 2. Service Availability Information 3. Facility Availability 4. Street Address Validation 5. Customer Service Records 6. Telephone Number 7. Loop Qualification Tools ^{NOTE 3} 8. Resale of Qwest DSL Qualification 9. Connecting Facility Assignment ^{NOTE 4} 10. Meet Point Inquiry ^{NOTE 5} <p>For PO-1A (transactions via IMA-GUI), in addition to reporting total response time, response times for each of the above transactions will be reported in two parts: (a) time to access the request screen, and (b) time to receive the response for the specified transaction. For PO-1A 6, Telephone Number, a third part (c) accept screen, will be reported.</p> <p>For PO-1B (transactions via IMA-EDI), request/response will be reported as a combined number.</p> <p>PO-1C Results for PO-1C will be reported according to the gateway interface used:</p> <ol style="list-style-type: none"> 1. Percent of Preorder Transactions that Timeout IMA-GUI 2. Percent of Preorder Transactions that Timeout IMA-EDI <p>PO-1D Results for PO-1D will be reported according to the gateway interface used:</p> <ol style="list-style-type: none"> 1. Rejected Response Times for IMA-GUI 2. Rejected Response Times for IMA-EDI
<p>Formula:</p> <p>PO-1A & PO-1B = $\Sigma[(\text{Query Response Date \& Time}) - (\text{Query Submission Date \& Time})] \div (\text{Number of Queries Submitted in Reporting Period})$</p> <p>PO-1C = $[(\text{Number of IRTM Queries measured by PO-1A \& 1B that Timeout before receiving response}) \div (\text{Number of IRTM Queries Transmitted in Reporting Period})] \times 100$</p> <p>PO-1D = $\Sigma[(\text{Rejected Query Response Date \& Time}) - (\text{Query Submission Date \& Time})] \div (\text{Number of Rejected Query Transactions Simulated by IRTM})$</p>	
<p>Exclusions:</p> <p>PO-1A & PO-1B:</p> <ul style="list-style-type: none"> • Rejected requests/errors, and timed out transactions <p>PO-1C:</p> <ul style="list-style-type: none"> • Rejected requests and errors <p>PO-1D:</p> <ul style="list-style-type: none"> • Timed out transactions 	

PO-1 – Pre-Order/Order Response Times (continued)

Product Reporting: None	Standards: Total Response Time:	IMA-GUI	IMA-EDI
	1. Appointment Scheduling	<10 seconds	<10 seconds
	2. Service Availability Information	<25 seconds	<25 seconds
	3. Facility Availability	<25 seconds ⁶	<25 seconds ⁶
	4. Street Address Validation	<10 seconds	<10 seconds
	5. Customer Service Records	<12.5 seconds ⁶	<12.5 seconds ⁶
	6. Telephone Number	<10 seconds	<10 seconds
	7. Loop Qualification Tools NOTE ³	≤ 20 seconds ⁷	≤ 20 seconds
	8. Resale of Qwest DSL Qualification	≤ 20 seconds ⁷	≤ 20 seconds
	9. Connecting Facility Assignment	≤ 25 seconds	≤ 25 seconds
	10. Meet Point Inquiry	≤ 30 seconds	≤ 30 seconds
	PO-1C-1	0.5%	
	PO-1C-2	0.5%	
	PO-1D-1 & 2	Diagnostic	
Availability: Available	Notes: <ol style="list-style-type: none"> 1. Rejected query types used in PO-1D are those developed for internal Qwest diagnostic purposes. 2. As additional transactions, currently done manually, are mechanized, they will be measured and added to or included in the above list of transactions, as applicable. 3. Results based on a weighted combination of ADSL Loop Qualification and Raw Loop Data Tool. 4. Results based on Connecting Facility Assignment by Unit Query. 5. Results based on meet Point Query, POTS Splitter option for Shared loops. 6. Times reflect non-complex services, including residential, simple business, or POTS account. Does not include ADSL or accounts >25 lines. 7. Benchmark applies to response time only. Request time and Total time will also be reported. 		

PO-2 – Electronic Flow-through

<p>Purpose: Monitors the extent Qwest's processing of CLEC Local Service Requests (LSRs) is completely electronic, focusing on the degree that electronically-transmitted LSRs flow directly to the service order processor without human intervention or without manual retyping.</p>	
<p>Description: PO-2A - Measures the percentage of all electronic LSRs that flow from the specified electronic gateway interface to the Service Order Processor (SOP) without any human intervention.</p> <ul style="list-style-type: none"> Includes all LSRs that are submitted electronically through the specified interface during the reporting period, subject to exclusions specified below. <p>PO-2B – Measures the percentage of all flow-through-eligible LSRs ^{NOTE 1} that flow from the specified electronic gateway interface to the SOP without any human intervention.</p> <ul style="list-style-type: none"> Includes all flow-through-eligible LSRs that are submitted electronically through the specified interface during the reporting period, subject to exclusions specified below. 	
<p>Reporting Period: One month</p>	<p>Unit of Measure: Percent</p>
<p>Reporting Comparisons: CLEC aggregate, individual CLEC</p>	<p>Disaggregation Reporting: Statewide level (per multi-state system serving the state). Results for PO-2A and PO-2B will be reported according to the gateway interface* used to submit the LSR:</p> <ol style="list-style-type: none"> LSRs received via IMA-GUI LSRs received via IMA-EDI <p>*CO also reports an aggregate of IMA-GUI and IMA-EDI results.</p>
<p>Formula: PO-2A = $[(\text{Number of Electronic LSRs that pass from the Gateway Interface to the SOP without human intervention}) \div (\text{Total Number of Electronic LSRs that pass through the Gateway Interface})] \times 100$</p> <p>PO-2B = $[(\text{Number of flow-through-eligible Electronic LSRs that actually pass from the Gateway Interface to the SOP without human intervention}) \div (\text{Number of flow-through-eligible Electronic LSRs received through the Gateway Interface})] \times 100$</p>	
<p>Exclusions:</p> <ul style="list-style-type: none"> Rejected LSRs and LSRs containing CLEC-caused non-fatal errors. Non-electronic LSRs (e.g., via fax or courier). Records with invalid product codes. Records missing data essential to the calculation of the measurement per the PID. Duplicate LSR numbers. (Exclusion to be eliminated upon implementation of IMA capability to disallow duplicate LSR #'s.) Invalid start/stop dates/times. 	

PO-2 – Electronic Flow-through (continued)

<p>Product Reporting:</p> <ul style="list-style-type: none"> • Resale • Unbundled Loops (with or without Local Number Portability) • Local Number Portability • UNE-P (POTS) and UNE-P (Centrex 21) • Line Sharing 	<p>Standards:</p> <p>PO-2A: CO: CO PO-2B benchmarks minus 10 percent ^{NOTE 2} All Other States: Diagnostic</p> <p>PO-2B: ^{NOTE 2}</p> <table border="1" data-bbox="645 442 1430 612"> <tr> <td>Resale:</td> <td>95%</td> </tr> <tr> <td>Unbundled Loops:</td> <td>85%</td> </tr> <tr> <td>LNP:</td> <td>95%</td> </tr> <tr> <td>UNE-P (POTS & Centrex 21):</td> <td>95%</td> </tr> <tr> <td>Line Sharing:</td> <td>Diagnostic ^{NOTE 3}</td> </tr> </table>	Resale:	95%	Unbundled Loops:	85%	LNP:	95%	UNE-P (POTS & Centrex 21):	95%	Line Sharing:	Diagnostic ^{NOTE 3}
Resale:	95%										
Unbundled Loops:	85%										
LNP:	95%										
UNE-P (POTS & Centrex 21):	95%										
Line Sharing:	Diagnostic ^{NOTE 3}										
<p>Availability: Available (except as follows):</p> <p>Combined reporting of UNE-P (POTS) and UNE-P (Centrex 21) – beginning with Jul 04 data on the Aug 04 report.</p> <p>Line Sharing – beginning with Jul 04 data on the Aug 04 report</p>	<p>Notes:</p> <ol style="list-style-type: none"> 1. The list of LSR types classified as eligible for flow through is contained in the “LSRs Eligible for Flow Through” matrix. This matrix also includes availability for enhancements to flow through. Matrix will be distributed through the CMP process. 2. In Colorado the standard for PO-2 is considered met if the standard for either PO-2A or PO-2B is met. For both PO-2A and PO-2B, the benchmark percentages shown apply to the aggregations of PO-2A-1 and PO-2A-2 (i.e., the combined PO-2A result) and of PO-2B-1 and PO-2B-2 (i.e., the combined PO-2B result). 3. The standard and future disaggregated reporting of the Line Sharing product is TBD, pending resolution of TRO issues. 										

PO-3 – LSR Rejection Notice Interval

Purpose: Monitors the timeliness with which Qwest notifies CLECs that electronic and manual LSRs were rejected.	
Description: Measures the interval between the receipt of a Local Service Request (LSR) and the rejection of the LSR for standard categories of errors/reasons. <ul style="list-style-type: none"> • Includes all LSRs submitted through the specified interface that are rejected during the reporting period. • Standard reasons for rejections are: missing/incomplete/mismatching/unintelligible information, duplicate request or LSR/PON (purchase order number), no separate LSR for each account telephone number affected, no valid contract, no valid end user verification, account not working in Qwest territory, service-affecting order pending, request is outside established parameters for service, and lack of CLEC response to Qwest question for clarification about the LSR. • Included in the interval is time required for efforts by Qwest to work with the CLEC to avoid the necessity of rejecting the LSR. • With hours: minutes reporting, hours counted are (1) business hours for manual rejects (involving human intervention) and (2) published Gateway Availability hours for auto-rejects (involving no human intervention). Business hours are defined as time during normal business hours of the Wholesale Delivery Service Centers, except for PO-3C in which hours counted are workweek clock hours. Gateway Availability hours are based on the currently published hours of availability found on the following website: http://www.qwest.com/wholesale/cmp/ossHours.html. 	
Reporting Period: One month	Unit of Measure: PO-3A-1, PO-3B-1 & PO-3C - Hrs: Mins. PO-3A-2 & PO-3B-2 – Mins: Secs.
Reporting Comparisons: CLEC aggregate and individual CLEC results	Disaggregation Reporting: Results for this indicator are reported according to the gateway interface used to submit the LSR: <ul style="list-style-type: none"> • PO-3A-1, LSRs received via IMA-GUI and rejected manually: Statewide • PO-3A -2, LSRs received via IMA-GUI and auto-rejected: Region wide • PO-3B-1, LSRs received via IMA-EDI and rejected manually: Statewide • PO-3B -2, LSRs received via IMA-EDI and auto-rejected: Region wide • PO-3C, LSRs received via facsimile: Statewide
Formula: $\frac{\sum [(Date\ and\ time\ of\ Rejection\ Notice\ transmittal) - (Date\ and\ time\ of\ LSR\ receipt)]}{(Total\ number\ of\ LSR\ Rejection\ Notifications)}$	
Exclusions: <ul style="list-style-type: none"> • Records with invalid product codes. • Records missing data essential to the calculation of the measurement per the PID. • Duplicate LSR numbers. (Exclusion to be eliminated upon implementation of IMA capability to disallow duplicate LSR #'s.) • Invalid start/stop dates/times. 	
Product Reporting: Not applicable (reported by ordering interface).	Standards: <ul style="list-style-type: none"> • PO-3A-1 and -3B-1: ≤ 12 business hours • PO-3A -2 and -3B -2: ≤ 18 seconds • PO-3C: ≤ 24 work week clock hours
Availability: <p style="text-align: center;">Available</p>	Notes:

